

A CubeSat GNSS Payload for Precise Orbit Determination and Maintenance

Other Conference Item**Author(s):**

Chen, Kangkang; Rothacher, Markus; Müller, Lukas; Kreiliger, Flavio; De Florio, Sergio; Lauber, Pierre

Publication date:

2020-11-10

Permanent link:

<https://doi.org/10.3929/ethz-b-000459698>

Rights / license:

In Copyright - Non-Commercial Use Permitted

Space Studies of the Earth's Surface, Meteorology and Climate (A)
CubeSats for Scientific and Civil-use Studies of the Earth (A0.5)
Consider for oral presentation.

A CUBESAT GNSS PAYLOAD FOR PRECISE ORBIT DETERMINATION AND MAINTENANCE

Mr. Kangkang Chen, kachen@ethz.ch
Swiss Federal Institute of Technology, Zurich, Zurich, Switzerland
Markus Rothacher
Institute of Geodesy and Photogrammetry, ETH Zurich, Zurich, Switzerland, markus.rothacher@ethz.ch
Lukas Müller
Institute of Geodesy and Photogrammetry, ETH Zurich, Zurich, Switzerland, lukamueller@ethz.ch
Flavio Kreiliger
Lucerne University of Applied Sciences and Arts, Lucerne, Switzerland, flavio.kreiliger@bluewin.ch
Sergio De Florio
Astrocast SA, Lausanne, Switzerland, sdeflorio@astrocast.com
Pierre Lauber
Astronomical Institute University of Bern, Bern, Switzerland, pierre.lauber@aiub.unibe.ch

Global Navigation Satellite Systems (GNSS) have been used as a key technology for satellite orbit determination for about 30 years. With the increasing popularity of miniaturized satellites (e.g., CubeSats that are nanosatellites based on standardized 10 cm-sized units) the need for an adapted payload for orbit determination arises. We developed a small-size versatile GNSS payload board using commercial off-the-shelf single-frequency GNSS receivers with extremely small weight (1.6 g), size (12.2 x 16.0 x 2.4 mm³) and power consumption (100 mW). The board features two separate antenna connectors and four GNSS receivers – two connected to each antenna. This redundancy lowers the risk of a total payload failure in case one receiver is malfunctioning. Two prototypes of the GNSS positioning board have been successfully launched onboard the Astrocast-01 and -02 3-unit cube satellites with altitudes of 575 and 505 km, respectively. In addition, both satellites are equipped with a small array of three laser retroreflectors enabling orbit validation with Satellite Laser Ranging (SLR). After the two precursor missions, a constellation of 80 satellites is planned, allowing the formation and computation of a highly uniform polyhedron in space with cm-accuracy, relevant for geocenter, reference frame, and GNSS orbit determination.

At present, we have continuous receiver PVT solutions available. The real-time onboard orbit determination results indicate that the receivers perform very well on both satellites. The RMS of a daily orbit fitting is, after removing one or the other outlier, at the level of 2-5 meters despite errors caused by the ionosphere and the orbit model. For a few satellite arcs the recording of GNSS raw phase and code data was enabled, allowing orbit determination in

a post-processing mode. This allows a better assessment of the achievable orbit quality and overall performance estimation. The tests performed so far include the improvement of the orbit quality by eliminating the ionospheric refraction based on a linear combination of phase and code observations, the comparison of various single-system solutions and advances in combining the different tracking systems for orbit determination. In collaboration with the Zimmerwald Observatory in Switzerland, a first SLR campaign was conducted that successfully tracked both nanosatellites. The SLR measurements with their high accuracy were then analyzed to validate the orbits of the Astrocast satellites derived from GNSS measurements. Astrocast satellite also carries small thrusters that are used for orbit maintenance. Precise estimation of the thrust force acting on satellite using GNSS data could be performed allowing a rigorous assessment of the thruster system.

We will present details on the orbit determination in real-time and in post-processing mode based on the low-cost single-frequency multi-GNSS receivers onboard the satellites, the SLR orbit validation, and the analysis of the actual maneuver performance.